

บริษัท อุดมกิจ ฟิตติ้ง วาล์ว จำกัด

UDOMKIT FITTING VALVE CO., LTD.



254/17 หมู่ 7 ถนนสุขสวัสดิ์ แขวงบางปะกอก เขตราษฎร์บูรณะ กรุงเทพฯ 10140

โทร. 0-2 4270952, 0-2 4282114-5, 0-2 8720520-2, แฟกซ์ 0-2 4282125

[HTTP://WWW.UDOMKIT.COM](http://www.udomkit.com)

EMAIL : UGROUPS@HOTMAIL.COM

ศูนย์รวมอุปกรณ์ ท่อ วาล์ว และวัสดุโรงงานทุกชนิด



STANDARD SPECIFICATIONS

Normal Diameter Range	50 to 300mm (2 to 12 inches)
Applicable Flange Standard	JIS:10k, 16k ANSI :125Lb,150 Lb
Service Pressure	Others 16 bar. / 232psi / 16kgf/cm ² , 8" lever 10 Bar only
Hydrostatic shell Test	17.6 bar. / 257psi / 18kgf/cm ²
Hydrostatic shell Test Service Temperature Range	24 bar. / 342psi / 24kgf/cm ² EPDM Seat Ring:-20 to 120°C NBR Seat Ring:-10 to 80°C
Actuators	Lever, Gear, Pneumatic Act., Electric Act.
Face to Face Dimensions	Conforms to ISO STANDARD (Short)
Actuator Mounting Flange	Conforms to ISO STANDARD
Standard coating	Polyurethane PU 1400-9700 Valve Blue M
Service Media	Water Oil, etc.

	Standard		Semi-Standard	
Seat Ring	JIS	ASTM	JIS	ASTM
	EPDM	EPDM	NBR	NBR
	SCS13	A351 CF8	Aluminium Bronze	(ASTM B148 C 95200)
Disc	-	-	SCS14	A351 CF8M
Body	FCD45	A536 65-45-12	FCD45	A536 65-45-12
Spindle(Stem)	SUS420J2	A276 403		
O-ring	NBR			
Ring	SUS 304			
Bush	Plastic			
Gasket	Asbestos-free			
Bottom Cover	Mild steel			